

Aluminum Twin Ramps Specifications

Model	Load Capacity		Height				Width Overall		Width Inside Curbs		Length		Weight Each Track	
			Max 11° Incline		Minimum 8° Incline									
	lbs	kg	in	cm	in	cm	in	cm	in	cm	ft	m	lbs	kg
ATWR-P-7-15-8	7000	3175	17.5	44.5	12.5	31.8	19	48.3	15	38.1	8	2.44	52	23.6
ATWR-P-5.5-15-10	5500	2495	22.5	57.2	16	40.6	19	48.3	15	38.1	10	3.05	64	29.0
ATWR-P-7-15-12	7000	3175	27.0	68.6	19	48.3	19	48.3	15	38.1	12	3.66	105	47.6
ATWR-P-6-15-14	6000	2722	32.0	81.3	22.5	57.2	19	48.3	15	38.1	14	4.27	120	54.4
ATWR-P-5.5-15-16	5500	2495	36.5	92.7	25.5	64.8	19	48.3	15	38.1	16	4.88	138	62.6
ATWR-P-6-15-18	6000	2722	41.0	104.1	29	73.7	20	50.8	15	38.1	18	5.49	170	77.1
ATWR-P-5.5-15-20	5500	2495	46.0	116.8	32.5	82.6	20	50.8	15	38.1	20	6.10	190	86.2
ATWR-P-5.5-15-24	5500	2495	55.5	141.0	39	99.1	20	50.8	15	38.1	24	7.32	250	113.4

We reserve the right to make specification, equipment and price changes without notice.