


Aluminum Walkramps (Apron Mount) Specifications

| Model | Load Capacity | | Height | | | | Width Overall | | Width Inside Curbs | | Length | | Weight | |
|--------------------------|---------------|------|-----------------|-------|--------------------|------|---------------|------|--------------------|------|--------|------|--------|------|
| | | | Max 20° Incline | | Minimum 8° Incline | | | | | | | | | |
| | lbs | kg | in | cm | in | cm | in | cm | in | cm | ft | m | lbs | kg |
| AWKR-P-2.5-24-6A | 2500 | 1134 | 22 | 55.9 | 10 | 25.4 | 24 | 61.0 | 22 | 59.9 | 6 | 1.83 | 55 | 24.9 |
| AWKR-P-2.5-26-6A | 2500 | 1134 | 22 | 55.9 | 10 | 25.4 | 26 | 66.0 | 24 | 61.0 | 6 | 1.83 | 58 | 26.3 |
| AWKR-P-2.5-32-6A | 2500 | 1134 | 22 | 55.9 | 10 | 25.4 | 32 | 81.3 | 30 | 76.2 | 6 | 1.83 | 66 | 29.9 |
| AWKR-P-2.5-38-6A | 2500 | 1134 | 22 | 55.9 | 10 | 25.4 | 38 | 96.5 | 36 | 91.0 | 6 | 1.83 | 75 | 34.0 |
| AWKR-P-2-24-8A | 2000 | 910 | 30 | 76.2 | 13 | 33.0 | 24 | 61.0 | 22 | 59.9 | 8 | 2.44 | 72 | 32.6 |
| AWKR-P-2-26-8A | 2000 | 910 | 30 | 76.2 | 13 | 33.0 | 26 | 66.0 | 24 | 61.0 | 8 | 2.44 | 76 | 34.5 |
| AWKR-P-2-32-8A | 2000 | 910 | 30 | 76.2 | 13 | 33.0 | 32 | 81.3 | 30 | 76.2 | 8 | 2.44 | 88 | 39.9 |
| AWKR-P-2-38-8A | 2000 | 910 | 30 | 76.2 | 13 | 33.0 | 38 | 96.5 | 36 | 91.0 | 8 | 2.44 | 100 | 45.3 |
| AWKR-P-1.7-24-10A | 1700 | 771 | 38 | 96.5 | 16 | 40.6 | 24 | 61.0 | 22 | 59.9 | 10 | 3.05 | 90 | 40.8 |
| AWKR-P-1.7-26-10A | 1700 | 771 | 38 | 96.5 | 16 | 40.6 | 26 | 66.0 | 24 | 61.0 | 10 | 3.05 | 95 | 43.1 |
| AWKR-P-1.7-32-10A | 1700 | 771 | 38 | 96.5 | 16 | 40.6 | 32 | 81.3 | 30 | 76.2 | 10 | 3.05 | 110 | 49.9 |
| AWKR-P-1.7-38-10A | 1700 | 771 | 38 | 96.5 | 16 | 40.6 | 38 | 96.5 | 36 | 91.0 | 10 | 3.05 | 124 | 56.3 |
| AWKR-P-1.5-24-12A | 1500 | 680 | 46 | 116.8 | 19 | 48.3 | 24 | 61.0 | 22 | 59.9 | 12 | 3.66 | 108 | 49.0 |
| AWKR-P-1.5-26-12A | 1500 | 680 | 46 | 116.8 | 19 | 48.3 | 26 | 66.0 | 24 | 61.0 | 12 | 3.66 | 114 | 51.7 |
| AWKR-P-1.5-32-12A | 1500 | 680 | 46 | 116.8 | 19 | 48.3 | 32 | 81.3 | 30 | 76.2 | 12 | 3.66 | 132 | 59.9 |
| AWKR-P-1.5-38-12A | 1500 | 680 | 46 | 116.8 | 19 | 48.3 | 38 | 96.5 | 36 | 91.0 | 12 | 3.66 | 149 | 67.6 |
| AWKR-P-1.3-24-14A | 1300 | 590 | 55 | 139.7 | 22 | 55.9 | 24 | 61.0 | 22 | 59.9 | 14 | 4.27 | 126 | 57.2 |
| AWKR-P-1.3-26-14A | 1300 | 590 | 55 | 139.7 | 22 | 55.9 | 26 | 66.0 | 24 | 61.0 | 14 | 4.27 | 133 | 60.3 |
| AWKR-P-1.3-32-14A | 1300 | 590 | 55 | 139.7 | 22 | 55.9 | 32 | 81.3 | 30 | 76.2 | 14 | 4.27 | 153 | 69.4 |
| AWKR-P-1.3-38-14A | 1300 | 590 | 55 | 139.7 | 22 | 55.9 | 38 | 96.5 | 36 | 91.0 | 14 | 4.27 | 174 | 78.9 |
| AWKR-P-1-24-16A | 1000 | 454 | 62 | 157.5 | 26 | 66.0 | 24 | 61.0 | 22 | 59.9 | 16 | 4.88 | 144 | 65.3 |
| AWKR-P-1-26-16A | 1000 | 454 | 62 | 157.5 | 26 | 66.0 | 26 | 66.0 | 24 | 61.0 | 16 | 4.88 | 152 | 68.9 |
| AWKR-P-1-32-16A | 1000 | 454 | 62 | 157.5 | 26 | 66.0 | 32 | 81.3 | 30 | 76.2 | 16 | 4.88 | 175 | 79.4 |
| AWKR-P-1-38-16A | 1000 | 454 | 62 | 157.5 | 26 | 66.0 | 38 | 96.5 | 36 | 91.0 | 16 | 4.88 | 198 | 89.8 |

Walkramps made with Checker Plate Deck also available. Please contact us for further information.
Hook Mount models also available – see table below.

| Hook Mount Model | | | | |
|--|---------------|------|------------------|------|
|  | Overall Width | | Spacing of Hooks | |
| | in | cm | in | cm |
| | 24 | 61.0 | 19 | 48.3 |
| | 26 | 66.0 | 21 | 53.3 |
| | 32 | 81.3 | 27 | 68.6 |
| 38 | 96.5 | 33 | 83.8 | |

We reserve the right to make specification, equipment and price changes without notice.